



GAVIN PUBLISHERS

### Review Article

## Efficient Removal of Heavy metals from Oil-field Produced Water: A Review of Currently Available Techniques

Rakhi N. Mehta<sup>1</sup> and Dayanand Saini<sup>2\*</sup>

<sup>1</sup>Chemical Engineering Department, Sarvajanik College of Engineering and Technology, Surat, India.

<sup>2</sup>Department of Physics & Engineering, California State University, Bakersfield, CA, USA.

**\*Corresponding author:** Dayanand Saini, Department of Physics and Engineering, California State University, Bakersfield, CA, USA, Tel: +661 654-2845; Fax +661 654-2693; Email: dsaini@csub.edu

**Citation:** Rakhi NM and Dayanand S (2017) Efficient Removal of Heavy metals from Oil-field Produced Water: A Review of Currently Available Techniques. Arch Petro Environ Biotechnol 2017: APEB-105

**Received Date:** 2 January, 2017; **Accepted Date:** 10 February, 2017; **Published Date:** 17 February, 2017

### Abstract

Oil and gas production operations from depleted oil and gas fields often result in the production of enormous amount of water. Even though, disposal of this oil-field produced water itself is a challenging task, however at the same time, treated oil-field produced water can provide an unconventional source of water that could be used for certain beneficial reuses.

The present study reports on the review of various currently available oil-field water treatment technologies with a focus on heavy metals removal technologies. It appears that the photo catalytic methods are the most promising methods for removing heavy metals from oil-field produced water. However, several factors including the initial metal concentration, the component of the wastewater, capital investment and operational cost, plant flexibility and reliability, environmental impact, and utility of the treated water have a great influence on the selection of the most suitable treatment techniques.

### Introduction

Extraction of oil and gas from underground reservoirs often is accompanied by water or brine, which is referred to as produced water. Produced water is the largest waste-stream of oil and gas exploration which includes water trapped in underground formations and water injected into the stratum to drive out the crude oil [1]. In early stages of oil production, water content is usually low but can rise to as high as 80% during the later years of the well [2]. As reservoirs mature, especially if secondary or tertiary recovery methods are used, the quantity of water climbs and often exceeds the volume of the hydrocarbons before the reservoir is exhausted. It has been observed that in some of the oil-fields this ratio is 1:15 where 15 parts of water accompany just 1 part of oil. Global produced water production is estimated at about 250 million barrels per day compared with about 80 million barrels per day of oil [3]. The chemical composition and behaviour of produced water

varies when compared with the surface waters because they are constrained within an aquifer and has distinctive characteristics due to the presence of organic and inorganic matters, high salinity, BTEX, PAH, heavy metals etc. which can cause toxicity to the environment [4]. Generally, produced water is composed of dissolved and dispersed oil components, dissolved formation minerals, production chemicals, dissolved gases (including CO<sub>2</sub> and H<sub>2</sub>S) and produced solids. There is a wide variation in the level of its organic and inorganic composition due to geological formation, lifetime of the reservoir and the type of hydrocarbon produced. Also, this produced water contains various microorganisms which result in microbial corrosion of the inner surfaces of pipes by forming bio films on the metal surfaces [5]. The constituents of produced water vary and can differ from well to well with pH in the range of 6-8.5 [6]. Produced water is increasingly being considered to supplement limited freshwater resources in many parts of the US as well

**Citation:** Rakhi NM and Dayanand S (2017) Efficient Removal of Heavy metals from Oil-field Produced Water: A Review of Currently Available Techniques. Arch Petro Environ Biotechnol 2017: APEB-105

as other countries [7]. The cost of producing, handling, and disposing of the produced water often defines the economic lifetime of a field and the actual hydrocarbon reserves; therefore, understanding and predicting the aspects, behaviour, and problems induced by the produced-water flow is important.

### Composition of oil-field produced water

Oil field produced water generally consists of dispersed and dissolved oil components those are mixture of hydrocarbons including BTEX (benzene, toluene, ethylbenzene and xylene), PAHs (polyaromatic hydrocarbons) and phenols. Dissolved oils are the polar constituent organic compounds in produced water, while small droplets of oil suspended in the aqueous phase are called dispersed oil [8-10]. BTEX, phenols, aliphatic hydrocarbons, carboxylic acid and low molecular weight aromatic compound are classified as dissolved oil, while less-soluble PAHs and heavy alkyl phenols are present in produced water as dispersed oil [11]. Dissolved and dispersed oil has to be removed in order to utilize this produced water for some efficient reuse.

Dissolved inorganic compounds or minerals are usually high in concentration, and classified as cations and anions, naturally occurring radioactive materials and heavy metals. Cations and anions play a significant role in the chemistry of produced water. Na and  $Cl_2$  are responsible for salinity, ranging from a few milligrams per litre to 300000 mg/L [12].  $Cl_2$ ,  $SO_4$ ,  $CO_3$ , HCO, Na, K,  $Ca_2$ ,  $Ba_2$ ,  $Mg_2$ ,  $Fe_2$  and  $Sr_2$  affect conductivity and scale-forming potential. Typical oilfield produced water contains heavy metals in varied concentrations, depending on the formation geology and the age of oil well and its concentration is usually higher than those of receiving water (for enhanced oil recovery) and those found in sea water [13]. 226Ra and 228Ra are the most abundant naturally occurring radioactive elements present sometimes in oilfield produced water [13]. Radioactivity of produced water results primarily from radium that is co-precipitated with barium sulphate (scale) or other types of scales [14].

### Current scenario of oil-field produced water disposal

At present, oil and gas operators manage the produced water by following one or more of the options. Some try to avoid production of water by blocking the water fractures by polymer gel or down hole water separator; but this option is not always possible as water would generally be produced during secondary and tertiary extraction process of oil. Another is injecting the produced water back into the formations. However, this demands transportation of water, and treatment to reduce fouling and bacterial growth. In the long term, the stored produced water may pollute the underground waters. Also, some follows its discharge in to the environment if it meets onshore and offshore discharge regulations. Petro-

leum industry may try reusing minimally treated produced water for drilling and work over operations. Finally, it could be utilized for beneficial domestic purposes such as for irrigation, wildlife consumption and industrial water, but this may involve significant treatment [3,15].

Environmental concerns and the prospect of beneficial uses have driven research into the treatment of produced water. Current conventional treatment technologies are targeted at removal of heavy metals, oil and grease, suspended solids, and desalination, which often lead to the generation of large volumes of secondary waste. For instance, heavy metals are removed as sludge using current treatment technologies [16]. This article reviews current produced water efficient, eco-friendly and cost effective treatment technologies for removal of heavy metals thereby rendering the produced water for reuse with minimal negative impact on the environment.

### Pre-treatment methods for oil-field produced waters

The first pre-treatment process of the oil-field produced waters containing traces of oil is the oil-water separation. The conventional rectangular-channel separators, developed by the American Petroleum Institute (API) are widely used for this purpose, and their design criteria are summarized in the publication API, 1990 [17]. Many other separators had been developed based on the oil-water separation theory and some of them, as the parallel plate and corrugated plate separators, had been implemented in the petroleum refineries [18]. The oil separators remove only the fraction of free oil, whereas the emulsified and the dissolved oil remain in the separator effluent in the form of oil-water emulsions. These emulsions could be destabilized using chemical de stabilizers followed by separation using dissolved air flotation technique (DAF) [19-21]. Different biological treatment processes that have been utilized for treating produced water are aerated ponds, activated sludge, biological contactors, sequential bath reactors and moving bed reactors [22-25]. Initial researches that had been done for recycling of the biologically treated refinery effluent involved the use of activated carbon adsorption alone or in combination with ozonation or sand filtration [26-28]. The membrane technology development allowed additional options, such as ultrafiltration and reverse osmosis [29-32]. The implementation of the advanced treatment technology allowed reusing of the biologically treated wastewater and freshwater savings in the refineries.

### Effects of heavy metals

Heavy metals are generally considered to be those whose density exceeds 5 g per cubic centimetre and atomic weights between 63.5 and 200.6. Most heavy metals are well-known toxic and carcinogenic agents and it represent a serious threat to the

**Citation:** Rakhi NM and Dayanand S (2017) Efficient Removal of Heavy metals from Oil-field Produced Water: A Review of Currently Available Techniques. Arch Petro Environ Biotechnol 2017: APEB-105

human population and the fauna and flora of the receiving water bodies. Heavy metals have a great tendency to bio-accumulate and end up as permanent additions to the environment and have detrimental effect on human health [33]. Once they enter the food chain, large concentrations of heavy metals may accumulate in the human body. If the metals concentrations are ingested beyond the permitted value, they can cause serious health disorders. A large number of elements fall into this category, but the ones discussed here are those of relevance in the environmental context. Arsenic is usually regarded as a hazardous heavy metal even though it is actually a semi-metal. Heavy metals cause serious health effects, including reduced growth and development, cancer, organ damage, nervous system damage, and in extreme cases, death. Exposure to some metals, such as mercury and lead, may also cause development of autoimmunity, in which a person's immune system attacks its own cells. This can lead to joint diseases such as rheumatoid arthritis, and diseases of the kidneys, circulatory system, nervous system, and damaging of foetus's brain. Wastewater regulations were established to minimize human and environmental exposure to hazardous chemicals. This includes limits on the types and concentration of heavy metals that may be present in the discharged wastewater [34-35].

### Produced water management techniques

The general objectives for operators treating produced water are: de-oiling (removal of dispersed oil and grease), desalination, removal of suspended particles (salts) and sand, removal of soluble organics, removal of dissolved gases, removing traces of heavy metals, removal of naturally occurring radioactive materials (NORM), disinfection and softening (to remove excess water hardness) [15]. In this current review, different methods to remove heavy metals from oil-field produced waters have been discussed in detail. These methods include chemical precipitation, coagulation, flocculation, ion-exchange, adsorption, membrane filtration, Reverse Osmosis, floatation, electrochemical treatment technologies, Electro dialysis, Photo catalysis and biological methods.

### Chemical Precipitation, Coagulation and Flocculation

The conventional method for heavy metal removal from industrial wastewater generally involves a chemical precipitation process [36-39]. Of the various treatment methods employed to remove heavy metals, hydroxide precipitation is the most common treatment technology. Heavy metals are removed by adding alkali such as caustic, lime or soda ash to adjust the wastewater pH to the point where the metals exhibit a minimum solubility. Then a proper solid-liquid separation technique removes the metal precipitation such as sedimentation and filtration. The conventional heavy metal removal process has some inherent shortcomings such as requiring a large area of land, a sludge dewatering facility, skilful

operators and multiple basin configurations [40]. The conceptual mechanism of heavy metal removal by chemical precipitation is presented in Eq. (1)  $M^{2+} + 2(OH)^- \leftrightarrow M(OH)_2$ , [41].

Where,  $M^{2+}$  and  $OH^-$  represent the dissolved metal ions and the precipitant, respectively, while  $M(OH)_2$  is the insoluble metal hydroxide. Adjustment of pH to the basic conditions (pH range of 9–11) is the major parameter that significantly improves heavy metal removal by chemical precipitation. Lime and limestone are the most commonly employed precipitant agents due to their availability and low-cost in most countries [42- 43]. Lime precipitation can be employed to effectively treat inorganic effluent with a metal concentration of higher than 1000 mg/L and other advantages of using lime precipitation include the simplicity of the process, inexpensive equipment requirement, and convenient and safe operations. To enhance lime precipitation, fly ash was used as a seed material [43]. The fly ash- lime carbonation treatment increased the particle size of the precipitate and improved the efficiency of heavy metal removal. In hydroxide precipitation process, the addition of coagulants such as alum, iron salts, and organic polymers can enhance the removal of heavy metals from wastewater. Another researcher employed chemical coagulation and precipitation by lime to treat synthetic wastewater [44]. Sulphide precipitation is also an effective process for the treatment of toxic heavy metal ions. One of the primary advantages of using sulphides is that the solubility's of the metal sulphide precipitates are dramatically lower than hydroxide precipitates and sulphide precipitates are not amphoteric. Also, this process can achieve a high degree of metal removal over a broad pH range compared with hydroxide precipitation. Metal sulphide sludge also exhibit better thickening and de watering characteristics than the corresponding metal hydroxide sludge. However, there are potential dangers in the use of sulphide precipitation process as it many times results into evolution of toxic  $H_2S$  fumes. However, chemical precipitation has been successful in combination with other methods and a reported literature shows that sulphide precipitation can reuse and recover heavy metal ions by employing nano filtration as a second step [45]. There are some reports on chemical precipitation in combination with ion-exchange treatments. Here nickel was removed with the help of ion-exchange in combination of chemical precipitation [46]. Another novel method is nucleation precipitation which is a simple cost effective method to strip off heavy metals in a fluidized sand bed. In operation, the metal-bearing wastewater is pumped through a fluidized sand column with a simultaneous injection of carbonate solution to raise pH metal precipitation to occur and then deposit on the sand surface (nucleated precipitation) rather than to form discrete metal original sand grains are 0.2-0.3mm in diameter, but quickly grow to a much larger size (up to 2 or 3mm) upon continuous coating of metal precipitates. The larger coated sand particles sink to the bed bottom from which they can be eas-

**Citation:** Rakhi NM and Dayanand S (2017) Efficient Removal of Heavy metals from Oil-field Produced Water: A Review of Currently Available Techniques. Arch Petro Environ Biotechnol 2017: APEB-105

ily removed and new sand can then be added from the top of the stripper. Since the coated particle contains a high level of metal mineral, they can be collected for mineral recovery [47]. However, chemical precipitation requires large amounts of chemicals to reduce metals to an acceptable level for discharge along with excessive sludge formation that requires further treatment, slow metal precipitation, poor settling, the aggregation of metal precipitates, and the long-term environmental impacts of sludge disposal [48]. Coagulation is one of the most important methods for wastewater treatment, but the main objects of coagulation are only the Hydrophobic colloids and suspended particles. Flocculation is the action of polymers to form bridges between the flocs and bind the particles into large agglomerates or clumps. Once suspended particles are flocculated into larger particles, they can usually be removed or separated by filtration, straining or floatation. Today many kinds of flocculants, such as PAC, poly ferric sulphate (PFS) and poly acryl amide (PAM), are widely used in the treatment of wastewater; however, it is nearly impracticable to remove heavy metal very well from wastewater directly by these current flocculants.

### Ion-Exchange Method

Ion exchange may be defined as the exchange of ions between the substrate and surrounding medium. The most useful ion exchange reaction is reversible, whereby the reaction is reversible and the ion exchanger can be regenerated and reused many times. Generally, resins are manufactured in the spherical, stress and strain free form to resist physical degradation. They are stable at high temperatures and applicable over a wide pH range. Ion exchange resins, which are completely insoluble in most aqueous and organic solutions, consist of across linked polymer matrix to which charged functional groups are attached by covalent bonds [49]. Typical ion exchangers are produced with a particle size distribution in the range 20-50mesh (for separation of anions from cations or of ionic species from non ionic ones). For more difficult separations, materials of smaller particle size or lower degrees of cross linking are necessary. Depending on the type of functional groups of exchanging certain ions, the ion exchangers with strongly acidic e.g., sulphonate  $-SO_3H$ , weakly acidic e.g, carboxylate  $-COOH$ , strongly basic e.g., quaternary ammonium  $-N^+R_3$  and weakly basic e.g., tertiary, and secondary amine  $-N^+R_2H$  and  $-N^+RH_2$  should be mentioned. The strong acidic cation exchangers are well dissociated over a wide pH range and thus reaching its maximum sorption capacity. There are also amphoteric exchangers, which depending on the pH of the solution may exchange either cations or anions. More recently these ion exchangers are called bipolar electrolyte exchange resins (BEE) or zwitter ionic ion exchangers [50].

Ion-exchange processes have been widely used to remove heavy metals from oil-field produced water and other waste waters

due to advantages such as high treatment capacity, high removal efficiency and fast kinetics [51]. Ion-exchange resin, either synthetic or natural solid resin, has the specific ability to exchange its cations with the metals in the wastewater; however, synthetic resins are commonly preferred as they are effective to nearly remove the heavy metals from the solution [52]. Hydrogen ions in the sulfonic group or carboxylic group of the resin can serve as exchangeable ions with metal cations. The uptake of heavy metal ions by ion-exchange resins is rather affected by certain variables such as pH, temperature, initial metal concentration and contact time [53]. Ionic charge also plays an important role in ion-exchange process which could be incurred from the study of removal of  $Ce_4$ ,  $Fe_3$  and  $Pb_2$  from aqueous systems by cation-exchange resin purolite C100 [54]. Similar results for  $Co_2$ ,  $Ni_2$  and  $Cr_3$  in an Amber lite IRN-77 cation exchange resin were previously obtained [55].

Besides synthetic resins, natural zeolites, naturally occurring silicate minerals, have been widely used to remove heavy metal from aqueous solutions due to their low cost and high abundance. Many researchers have validated that zeolites exhibit good cation-exchange capacities for heavy metal ions under different experimental conditions [56]. Clinoptilolite is one of the most frequently studied natural zeolites that have received extensive attention due to its selectivity for heavy metals. It has been studied that the surface of clinoptilolite loaded with amorphous Fe-oxide species would significantly improve its ion-exchange capacity [57]. Doula [57] employed clinoptilolite-Fe system to simultaneously remove Cu, Mn and Zn from drinking water and found that the system has very large metal adsorption capacity and for most of the cases the treated water samples were suitable for human consumption or agricultural use [58].

### Adsorption Method

Adsorption is now recognized as an effective and economic method for heavy metal wastewater treatment. The adsorption process offers flexibility in design and operation along with producing high-quality treated effluent. It is also very efficient because adsorption is sometimes reversible, adsorbents can be regenerated by suitable desorption process [59]. In recent years, the search for low cost adsorbents that have metal-binding capacities has been investigated [60]. The adsorbents may be of mineral, organic or biological origins, zeolites, industrial by-products, agricultural wastes, biomass, and polymeric materials [61]. Various other effective adsorbents are activated carbon, carbon nanotubes, low-cost adsorbents, bio adsorbents [59]. There are many adsorbents that can be used for the removal of metal ions from wastewater and, certainly, cost plays an important role for determining which one is applicable. Activated carbon (AC) adsorbents are widely used in the removal of heavy metal contaminants due to its large

**Citation:** Rakhi NM and Dayanand S (2017) Efficient Removal of Heavy metals from Oil-field Produced Water: A Review of Currently Available Techniques. Arch Petro Environ Biotechnol 2017: APEB-105

micro pore and meso pore volumes and the resulting high surface area. A large number of researchers are studying the use of AC for removing heavy metals [62].

Nowadays, the depleted source of commercial coal-based AC has resulted into increase in its price thereby opting other additives along with AC such as alginate, tannic acid and magnesium [63-65]. Converting carbonaceous materials into AC for heavy metals remediation have been reported. The use of AC from eucalyptus bark in the binary component sorption of Cu<sub>2</sub> and Pb<sub>2</sub> and poultry litter to manufacture AC for treating heavy metal-contaminated water was explored [66-67]. Carbon nanotubes (CNTs) discovered by Iijima [68], have been widely studied for their excellent properties and applications as new adsorbents possessing great potential for removing heavy metal ions such as lead [69], cadmium [70], chromium [71], copper and nickel [72] from waste water. CNTs are divided into two types: (1) single-walled CNTs (SWCNTs) and (2) multi-walled CNTs (MWCNTs) [73]. The mechanisms by which the metal ions are adsorbed onto CNTs are very complicated and appear attributable to electrostatic attraction, sorption-precipitation and chemical interaction between the metal ions and the surface functional groups of CNTs [74]. The sorption capacities of metal ions by raw CNTs are very low but significantly increase after oxidized by HNO<sub>3</sub>, NaClO and KMnO<sub>4</sub> solutions.

Despite these recently developed adsorbents the search for low cost and easily available adsorbents has become main research focus today. Studies have been carried out for adsorption of a few heavy metals on natural and modified kaolinite and montmorillonite [75], chemically modified plant wastes [76], industrial by-products such as lignin [77], diatomite [78], clino-pyrrhotite, lignite [79], aragonite shells [80], natural zeolites [81], clay [82], kaolinite and peat etc [83]. Another report showed zinc and copper removal from aqueous solutions using brine sediments, saw dust, and the mixture of both materials [84]. The potential to remove boron and arsenic from petrochemical wastewater by using aquatic booster was investigated in batch experiment process and the results were measured by inductively coupled plasma mass spectrometry (ICPMS). The main parameters influencing arsenic and boron adsorption onto the aquatic booster were contact time, size of particle, agitation speed, and dosage. The adsorption efficiency of arsenic and boron increases with longer contact time as well as more aquatic booster dosage and higher agitation speed. The removal efficiency for boron was around 60.36% by 35g/L dosage, 80 rpm and a particle size of 0.60 mm at of 390 minutes. As for the arsenic, the condition where it gives the removal percentage around 71.83% is that particle size of 0.6 mm, 300 minutes contact time, agitation speed of 80 rpm and dosage of 45g/L [85]. Hydrogels, which are cross linked hydrophilic polymers, a

recapable of expanding their volumes due to their high swelling in water and hence are being used in purification of wastewater. Various hydrogels were synthesized and their adsorption behavior for heavy metals was investigated while Barakat and Sahiner (2008) prepared poly (3-acrylamidopropyl) trimethyl ammonium chloride hydrogels for As (V) removal [86].

Biosorption of heavy metals from aqueous solutions is a relatively new process that is effective and inexpensive and has been confirmed a very promising process in the removal of heavy metal from dilute waste waters such as oil field produced water. Typical biosorbents can be derived from three sources as follows: (1) non-living biomass such as bark, lignin, shrimp, krill, squid, crab shell, etc (2) algal biomass; (3) microbial biomass, e.g. bacteria, fungi and yeast. Different forms of inexpensive, non-living plant material such as potato peels [87], sawdust [88], black gram husk [89], Rice husk [90-91], coffee husks [92], eggshell [93], seed shells [94], sugar-beet pectin gels [95] and citrus peels [96], sugarcane bagasse [97], coconut husk [98], oil palm shell [99], neem bark [100], fly ash have been widely investigated as potential biosorbents for heavy metals.

Algae, a renewable natural biomass proliferates ubiquitously and abundantly in the littoral zones of world has attracted the attention of many investigators as organisms to be tested and used as new adsorbents to adsorb metal ions. Several advantages in applying algae as biosorbent include the wide availability, low cost, high metal sorption capacity and reasonably regular quality. Research works on the metal biosorption using algal biomass include the biosorption of Cu<sub>2</sub> and Zn<sub>2</sub> using dried marine green macro alga Chaetomorpha [101], the biosorption of Cu<sub>2</sub>, Cd<sub>2</sub>, Pb<sub>2</sub> and Zn<sub>2</sub> using dried marine green macro alga Caulerpa [102], the biosorption of chromium from waste water using green alga Ulva lactuca [103], and the biosorption of lead (II) from wastewater by green algae Cladophora fascicularis [104]. Microbial removal of metal ions from wastewater has been indicated as being highly effective. Biosorption of heavy metals in aqueous solutions by bacteria includes Bacillus cereus [105], Escherichia coli [106], Pseudomonas aeruginosa [107]. Fungi and yeasts are easy to grow, produce high yields of biomass and at the same time can be manipulated genetically and morphologically. Fungi biosorbents include *Aspergillus niger* [108], *Rhizopus arrhizus* [109], *Saccharomyces cerevisiae* [110] and *Lentinus edodes* [111].

### Membrane filtration

Membrane filtration technologies with different types of membranes show great promise for heavy metal removal for their high efficiency, easy operation and space saving. The membrane processes used to remove metals from the wastewater are ultrafil-

**Citation:** Rakhi NM and Dayanand S (2017) Efficient Removal of Heavy metals from Oil-field Produced Water: A Review of Currently Available Techniques. Arch Petro Environ Biotechnol 2017: APEB-105

tration, reverse osmosis, nano filtration and electro dialysis.

Ultrafiltration (UF) is a membrane technique working at low transmembrane pressures for the removal of dissolved and colloidal material. Since the pore sizes of UF membranes are larger than dissolved metal ions in the form of hydrated ions or as low molecular weight complexes, these ions would pass easily through UF membranes, hence to obtain high removal efficiency of metal ions, then micellar enhanced ultra filtration (MEUF) and polymer enhanced ultra filtration (PEUF) was proposed. MEUF was first introduced by Scamehorn et al. in the 1980s for the removal of dissolved organic compounds and multivalent metal ions from aqueous streams [112]. This separation technique is based on the addition of surfactants to wastewater in a quantity beyond its critical micelle concentration (CMC), the surfactant molecules will aggregate into micelles that can bind metal ions to form large metal-surfactant structures. The micelles containing metal ions can be retained by a UF membrane with pore sizes smaller than micelle sizes, whereas the untrapped species readily pass through the UF membrane. To obtain the highest retentions, surfactants of electric charge opposite to that of the ions to be removed must be used and metal removal efficiency by MEUF depends on the characteristics and concentrations of the metals and surfactants, solution pH, ionic strength, and parameters related to membrane operation. PEUF uses water-soluble polymer to complex metallic ions and forms macromolecular, having a higher molecular weight than the molecular weight cut off of the membrane which will be retained when they are pumped through UF membrane. The reverse osmosis (RO) process uses a semi-permeable membrane, allowing the fluid that is being purified to pass through it, while rejecting the contaminants and accounts for more than 20% of the world's desalination capacity [113].  $\text{Cu}_2$  and  $\text{Ni}_2$  ions were successfully removed by the RO process and the rejection efficiency of the two ions increased up to 99.5% by using  $\text{Na}_2$ -EDTA [114]. The major drawback of RO is the high-power consumption due to the pumping pressures, and the restoration of the membranes. Nano filtration (NF) is the intermediate process between UF and RO and is a promising technology for the rejection of heavy metal ions such as nickel [115], chromium [116], copper [117], and arsenic [118] from wastewater. NF process benefits from ease of operation, reliability and comparatively low energy consumption as well as high efficiency of pollutant removal; however reports have been published on use of NF and RO in combination for removal of copper from process waste water [119]. Electro dialysis (ED) is another membrane process for the separation of ions across charged membranes from one solution to another using an electric field as the driving force where ion-exchange membranes are used. This process has been widely used for the production of drinking and process water from brackish water and sea water, treatment of in-

dustrial effluents, recovery of useful materials from effluents and salt production [120].

### Flotation Process

Flotation has nowadays found extensive use in waste water treatment and has been employed to separate heavy metals from a liquid phase using bubble attachment originated in mineral Processing. Dissolved air flotation (DAF), ion flotation and precipitation flotation are the main flotation processes for the removal of metal ions from solution. DAF is to allow micro-bubbles of air to attach to the suspended particles in the water, developing agglomerates with lower density than water, causing the flocs to rise through the water and accumulating at the surface where they can be removed as sludge [121]. Ion flotation method is based on imparting the ionic metal species in wastewaters hydrophobic by use of surfactants and subsequent removal of these hydrophobic species by air bubbles [122]. Potential of ion flotation was investigated to remove cadmium, lead and copper from dilute aqueous solution with a plant-derived biosurfactant tea sap on in [123]. Precipitate flotation process is another alternative of flotation method, based on the formation of precipitate and subsequent removal by attachment to air bubbles. Depending on the concentration of the metal solution, the precipitation may proceed by formation of metal hydroxide or as a salt with a specific anion (sulfide, carbonate, etc.) [124].

### Electrochemical method

Electrochemical methods involve the plating-out of metal ions on a cathode surface and can recover metals in the elemental metal state; however these wastewater treatment technologies involve relatively large capital investment and the expensive electricity supply, so they haven't been widely applied. Electro coagulation (EC) involves the generation of coagulants *in situ* by dissolving electrically either aluminum or iron ions from aluminum or iron electrodes where, metal ion generation takes place at the anode, and hydrogen gas is released from the cathode that helps to float the flocculated particles out of the water [125]. This technique has been used with aluminium electrodes for removing  $\text{Zn}_2$ ,  $\text{Cu}_2$ ,  $\text{Ni}_2$ , Ag and  $\text{Cr}_2\text{O}_7$  [126]. Electro flotation (EF) is a solid/liquid separation process that floats pollutants to the surface of a water body by tiny bubbles of hydrogen and oxygen gases generated from water electrolysis. EF has wide range applications in heavy metals removal from industrial wastewater and application of the optimized parameters on the separation of some heavy metal ions such as iron, nickel, copper, zinc, lead and cadmium was studied [127]. The Electro deposition has been usually applied for the recovery of metals from wastewater and is called a "clean" technology with no presence of the permanent residues for the separation

**Citation:** Rakhi NM and Dayanand S (2017) Efficient Removal of Heavy metals from Oil-field Produced Water: A Review of Currently Available Techniques. Arch Petro Environ Biotechnol 2017: APEB-105

of heavy metals [128].

### Photocatalysis Process

In the recent years, photo catalytic process in aqueous suspension of semiconductor has received considerable attention in view of solar energy conversion and this photo catalytic process was achieved for rapid and efficient destruction of environmental pollutants. Upon illumination of semiconductor-electrolyte interface with light energy greater than the semiconductor band gap, electron-hole pairs ( $e^-/h^+$ ) are formed in the conduction and the valence band of the semiconductor, respectively [129]. These charge carriers which migrate to the semiconductor surface, are capable of reducing or oxidizing species in solution having suitable redox potential. Various semiconductors have been used:  $TiO_2$ ,  $ZnO$ ,  $CeO_2$ ,  $CdS$ ,  $ZnS$ , etc. also a study showed photo catalytic degradation using UV-irradiated  $TiO_2$  suspension for destroying complex cyanide with a con-current removal of copper [130].

Several studies were reported for the photo catalytic reduction of Cr (VI), which is mobile and highly toxic, compared to Cr (III), which is immobile and less harmful. Heterogeneous photo catalytic oxidation of arsenite toarsenate in aqueous  $TiO_2$  suspensions has also been proved recently to be an effective and environmentally acceptable technique for the remediation of arsenite contaminated water. The process was performed using an adsorbent developed by loading iron oxide and  $TiO_2$  on municipal solid waste meltedslag [131].

### Biological methods

Various biological treatments, both aerobic and anaerobic can be used for heavy metal removal. A fixed activated sludge system (FAS) for treatment of wastewater containing heavy metal compounds (chromium, lead and nickel was carried out [132]. There results showed that a reduction of 84%, 75% and 80%, respectively was observed in chromium, lead and nickel on using fixed activated sludge at concentration of 1 mg/L. However, a reduction of 90%, 84% and 87%, respectively was observed by increasing concentration of them to 5 mg/L. Mechanism of activated sludge process was studied which showed that the carboxylic and amino groups are two main groups responsible for the binding properties of the biomass [133]. A novel bio filtration technique was utilized for the treatment of heavy metals mainly nickel, and their mechanism for heavy metals removal along with the kinetics of bio filters and its modeling aspects were studied [134]. The success in microbial cloning technique may improve the removal efficiency and hence the reduction in treatment cost. Trickling filter was used for removal of heavy metals, whereby the indigenous bacterial populations provided a certain advantage

and ensured durability under various operating conditions. They operated the system in three different ways i.e. batch, continuous and sequencing batch reactor (SBR) with recirculation [135]. The use of an attached growth system provides the necessary surface for the development of bio film structures. Bio films provide high biomass concentration per unit volume, while bacteria can remain in the reactor for unlimited time, thus allowing the bacteria better adjustment to the environmental conditions. The studies on the metal removal from an aerobically digested sludge by chemical treatment and microbial leaching processes in laboratory reactors were carried out by addition of ferric sulphate that resulted into acidification of the sludge and elution of heavy metals from the sludge [136]. The investigation also showed that with an increase in the amount of iron added and decrease in the sludge concentration, the pH of the sludge decreased. They also observed that the Ferric iron eluted cadmium, copper and zinc effectively than sulphuric acid. This chemical method was found to be useful for the removal of heavy metals from aerobically digested sewage sludge. Attached growth waste stabilization ponds were used for heavy metal removal where experiments were conducted to investigate the performance of AGWSP units that received Cd and Cr shock loadings. Per the investigation, the waste stabilization pond (WSP) units without attached-growth media had more concentrations of the applied heavy metals present in the effluents than waste stabilization ponds [137].

### Conclusions

Wastewater systems containing heavy metals with other organic pollutants, the presence of one species usually impedes the removal of the other. For instance, hydrometallurgy, a classical process to recover metals, is inhibited by the presence of organic compounds and a pre-treatment step, to remove or destroy organics, is generally required, pyro metallurgy which can decontaminate systems from organic pollutants and recover metals suffers from lack of controllability, demanding extremely high temperatures. The most promising methods to treat such complex systems are the photo catalytic ones which consume cheap photons from the UV-near visible region. These photo catalysts serve as electron relays, from the organic substrates to metal ions. Thus, they induce both degradation of organic pollutants and recovery of metals in one-pot systems, operable at traces of the target compounds (less than ppm). Although all above techniques can be employed for the treatment of heavy metal wastewater, it is important to mention that the selection of the most suitable treatment techniques depends on the initial metal concentration, the component of the wastewater, capital investment and operational cost, plant flexibility and reliability, environmental impact, utility of the treated water etc.

**Citation:** Rakhi NM and Dayanand S (2017) Efficient Removal of Heavy metals from Oil-field Produced Water: A Review of Currently Available Techniques. Arch Petro Environ Biotechnol 2017: APEB-105

## References

1. Deng S, Chen BR, Jian JP, Yu Z, Zhou G, et al. (2002) Produced water from polymer flooding process in crude oil extraction: Characterization and treatment by a novel cross flow oil-water separator. *Separation and Purification Technology* 29: 207-216.
2. Lu J, Wang X, Shan B, Li X, Wang W (2006) Analysis of chemical compositions contributable to Chemical Oxygen Demand (COD) of oilfield produced water. *Chemosphere* 62: 322-331.
3. Fakhru'l-Razi A, Pendashteh A, Abdullah LC, Biak DR, Madaeni SS, et al. (2009) Review of technologies for oil and gas produced water treatment. *J Hazard Mater* 170: 530-551.
4. Wemedo SA, Akani NP, Eke CE (2009) Fungi in an oilfield wastewater in Nigeria. *Asian J Biol Sci* 2: 54-57.
5. Puyate YT, Rim-Rukeh A (2008) 2D model for diffusion of oxygen with biochemical reaction during bio film formation process in static aqueous medium. *J Applied Sci* 8 : 1560-1565.
6. Cakmakce M, Kayaalp N, Koyuncu I (2008) Desalination of produced water from oil production fields by membrane processes. *Desalination* 222: 176-186.
7. Xu P, Drewes JE, Heil D (2008) Beneficial use of co-produced water through membrane treatment: Technical-economic assessment. *Desalination* 225: 139-155.
8. Hayes T, Arthur D (2004) Overview of emerging produced water treatment technologies. In: *The 11th Annual International Petroleum Environmental Conference*, Albuquerque, NM.
9. Khosravi J, Alamdari A (2009) Copper removal from oil-field brine by co precipitation. *J Hazard Mater* 166:695–700.
10. Stephenson MT, Ray JP, Engelhardt FR (1992) A survey of produced water studies. *Produced Water: Technological/Environmental Issues and Solutions*. Plenum Publishing Corp 1-12.
11. Veil JA, Puder MG, Elcock D, Redweik RJ Jr (2004) A White Paper Describing Produced Water from Production of Crude oil, Natural Gas, and Coal Bed Methane. US. D. o. E, Argonne National Laboratory.
12. Roach RW, Carr RS, Howard CL, Cain BW (1993) An assessment of produced water impacts at two sites in the Galveston Bay system. United States Fish and Wildlife Service, Clear Lake Field Office unpublished report. Houston, Texas.
13. Utvik TIR (2003) Composition, characteristics of produced water in the North Sea. In: *Produced Water Workshop*, Aberdeen, Scotland.
14. Jerez Vegueria SF, Godoy JM, Miekeley N (2002) Environmental impact studies of barium and radium discharges by produced waters from the 'Bacia de Campos' oil-field offshore platforms, Brazil. *J Environ Radioactivity* 62: 29-38.
15. Daniel Arthur J, Langhus BG, Patel C (2005) Technical Summary of Oil & Gas Produced Water Treatment Technologies. NETL.
16. Khosravi J, Alamdari A (2009) Copper removal from oil-field brine by coprecipitation. *J Hazard Mater*166: 695-700.
17. API (American Petroleum Institute) (1990) Design and operation of oil-water separators. API Publication. Washington D.C.
18. WEF (Water Environment Federation) (1994) Pretreatment of industrial wastes. Manual of Practice FD-3, Alexandria, USA
19. Eckenfelder WW (2000) *Industrial Water Pollution Control*, 3rd ed, McGraw-Hill.
20. Galil N, Wolf D (2001) Removal of hydrocarbons from petrochemical wastewater by dissolved air flotation. *Water Sci Technol* 43: 107-113.
21. Al-Shamrani AA, James A, Xiao H (2002) Destabilisation of oil-water emulsions and separation by dissolved air flotation. *Water Research* 36:1503-1512.
22. Galil N, Rebhum M (1992) Waste management solutions at an integrated oil refinery based on recycling of water, oil and sludge. *Water Science and Technology* 25:101-106.
23. Baron C, Equihua LO, Mestre JP (2000) B.O.O.Case: water management project for the use of reclaimed wastewater and desalted sea-water for the "Antonio Dovali Jayme" refinery, Salina Cruz, Oaxaca, Mexico. *Water Science and Technology* 42: 29-36.
24. Lee LY, Hu JY, Ong SL, Ng WJ, Ren JH, et al. (2004) Two stage SBR for treatment of oil refinery wastewater. *Water Science and Technology* 50: 243-249.
25. Schneider EE, Cerqueira ACFP, Dezotti M (2011) MBBR evaluation for oil refinery wastetreatment with post-ozonation and BAC, for water reuse. *Water Science and Technology* 63: 143-148
26. Misković D, Dalmacija B, Živanovž, Karlović E, Hain Z, et al. (1986) An investigation of the treatment and recycling of oil refinery wastewater. *Water Science and Technology* 18: 105-114.
27. Guarino CF, Da-Rin BP, Gazen A, Goettems EP (1988) Activated carbon as an advanced treatment for petrochemical wastewaters. *Water Science and Technology* 20:115-130.
28. Farooq S, Misbahuddin M (1991) Activated carbon adsorption and ozone treatment of a petrochemical wastewater. *Environmental Technology* 12:147-159.
29. Zubarev SV, Alekseeva NA, Ivashentsev VN, Yavshits GP, Matyushkin, et al. (1989) Purification of wastewater in petroleum refining industries by membrane methods. *Chemistry and Technology of Fuels and Oils* 25: 588-592.
30. Elmaleh S, Ghaffor N (1996) Upgrading oil refinery effluents by cross-flow ultrafiltration. *Water Science and Technology* 34: 231-238.
31. Teodosiu CC, Kennedy MD, van Straten HA, Schippers JC (1999) Evaluation of secondary refinery effluent treatment using ultrafiltration membranas. *Water Research* 33: 2172-2180.
32. Wang D, Tong F, Aerts P (2011) Application of the combined ultrafiltration and reverse osmosis for refinery wastewater reuse in Sinopec Yanshan Plant. *Desalination and Water Treatment* 25: 133-142.
33. Dhokpande SR and Kaware JP (2013) Biological Methods for Heavy Metal Removal- A Review, *International Journal of Engineering Science and Innovative Technology (IJESIT)* 2.
34. Babel S, Kurniawan TA (2003) Low-cost adsorbents for heavy metals uptake from contaminated water: a review. *J Hazard Mater* 97: 219-243.
35. Babel S, Kurniawan TA (2003) various treatment technologies to remove arsenic and mercury from contaminated groundwater: an overview. In: *Proceedings of the First International Symposium on South-east Asian Water Environment*, Bangkok, Thailand 24-25: 433-440.
36. Kim BM (1981) Treatment of metal-containing waste-water with cal-



<p><b>Citation:</b> Rakhi NM and Dayanand S (2017) Efficient Removal of Heavy metals from Environ Biotechnol 2017: APEB-105</p>	<p>Oil-field Produced Water: A Review of Currently Available Techniques. Arch Petro</p>
<p>cium sul@de. AICHE Symp 77: 39-48.</p> <p>37. Basta N (1983) Getting the metal out of spent plating baths. Chem Eng 90: 22-25.</p> <p>38. Thomas E H, Vernon E S (1984) Combined removal of Cr, Cd and Ni from wastes. Environ. Prog 3:12-25.</p> <p>39. Chowdhury J (1987) New routes buoy efforts to trim heavy-metal wastes. Chem Eng 94: 26-27.</p> <p>40. Zhou P, Huang JC, Alfred M, Li WF, Wei S (1999) heavy metal removal from wastewater in fluidized bed reactor. Wat Res 33: 1918-1924.</p> <p>41. Wang LK, Vaccari DA, Li Y, Shammass NK (2004) Chemical precipitation. In: Wang, L.K., Hung, Y.T., Shammass, N.K. (Eds.), Physicochemical Treatment Processes, Humana Press, New Jersey 3: 141-198.</p> <p>42. Mirbagherp SA and Hosseini SN (2004) Pilot plant investigation on petrochemical wastewater treatment for the removal of copper and chromium with the objective of reuse. Desalination 171: 85-93.</p> <p>43. Chen CL, Hu J, Shao DD, Li JX, Wang XK (2009) Adsorption behavior of multiwall carbon nanotube/iron oxide magnetic composites for Ni(II) and Sr(II). J Hazard Mater 164: 923-928.</p> <p>44. Charemtanyarak L (1999) Heavy metals removal by chemical coagulation and precipitation. Wat Sci Technol 39: 135-138.</p> <p>45. González-Muñoz MJ, Rodríguez MA, Luquea S, Álvarez JR (2006) Recovery of heavy metals from metal industry waste waters by chemical precipitation and nanofiltration. Desalination 200: 742-744.</p> <p>46. Papadopoulos A, Fatta D, Parperis K, Mentzis A, Haralambous KJ, Loizidou M (2004) Nickel uptake from a wastewater stream produced in a metal finishing industry by combination of ion-exchange and precipitation methods. Sep Purif Technol 39: 181-188.</p> <p>47. Huang JC (2005) Nucleated precipitation for heavy metal removal and resource recovery, Science Council of Asia, May 12th.</p> <p>48. Aziz HA, Adlan MN, Ariffin KS (2008) Heavy metals (Cd, Pb, Zn, Ni, Cu and Cr(III)) removal from water in Malaysia: post treatment by high quality limestone. Bioreso Technol 99: 1578- 1583.</p> <p>49. Sherrington DC (1998) Preparation, structure and morphology of polymer supports, Chemical Communications 30: 2275-2286.</p> <p>50. Nesterenko PN, Haddad PR (2000) Zwitterionic ion-exchangers in liquid chromatography, Analytical Sciences 16: 565-574.</p> <p>51. Kang SY, Lee JU, Moon SH, Kim KW (2004) Competitive adsorption characteristics of Co<sup>2+</sup>, Ni<sup>2+</sup>, and Cr<sup>3+</sup> by IRN-77 cation exchange resin in synthesized wastewater. Chemosphere 56: 141-147.</p> <p>52. Alyüz B, Veli S (2009) Kinetics and equilibrium studies for the removal of nickel and zinc from aqueous solutions by ion exchange resins. J Hazard Mater 167: 482-488.</p> <p>53. Gode F, Pehlivan E (2006) Removal of chromium (III) from aqueous solutions using Lewatit S 100: the effect of pH, time, metal concentration and temperature. J Hazard Mater 136: 330-337.</p> <p>54. Abo-Farha SA, Abdel-Aal AY, Ashourb IA, Garamon SE (2009) Removal of some heavy metal cations by synthetic resin purolite C100. J. Hazard. Mater 169: 190-194.</p> <p>55. Kang SY, Lee JU, Moon SH, Kim KW (2004) Competitive adsorption characteristics of Co<sup>2+</sup>, Ni<sup>2+</sup>, and Cr<sup>3+</sup> by IRN-77 cation exchange resin in synthesized wastewater. Chemosphere 56: 141-147.</p>	<p>56. Motsi T, Rowson NA, Simmons MJH (2009) Adsorption of heavy metals from acid mine drainage by natural zeolite. Int J Miner Process 92: 42-48.</p> <p>57. Doula MK, Dimirkou A (2008) Use of an iron-overexchanged clinoptilolite for the removal of Cu<sup>2+</sup> ions from heavily contaminated drinking water samples. J. Hazard. Mater 151: 738-745.</p> <p>58. Doula MK (2009) Simultaneous removal of Cu, Mn and Zn from drinking water with the use of clinoptilolite and its Fe-modified form. Water Res 43: 3659-3672.</p> <p>59. Fu F, Wang Q (2011) Removal of heavy metal ions from wastewaters: A review, Journal of Environmental Management 92: 407-418.</p> <p>60. Leung WC, Wong MF, Chua H, Lo W, Yu PH, et al. (2000) Removal and recovery of heavy metals by bacteria isolated from activated sludge treating industrial effluents and municipal wastewater. Water Sci Technol 41: 3.</p> <p>61. Kurniawan TA, Chan GYS, Lo WHS, Babel S (2005) Comparisons of low-cost adsorbents for treating wastewaters laden with heavy metals. Sci Total Environ 366:409.</p> <p>62. Jusoh A, Shiung LS, Ali N, Noor MJMM (2007) A simulation study of the removal efficiency of granular activated carbon on cadmium and lead. Desalination 206: 9-16.</p> <p>63. Park HG, Kim TW, Chae MY, Yoo IK, (2007) Activated carbon-containing alginate adsorbent for the simultaneous removal of heavy metals and toxic organics. Process Biochem 42: 1371-1377.</p> <p>64. Üçer A, Uyanik A, Aygün SF (2006) Adsorption of Cu (II), Cd(II), Zn(II), Mn(II) and Fe(III) ions by tannic acid immobilised activated carbon. Sep Purif Technol 47:113-118.</p> <p>65. Yanagisawa H, Matsumoto Y, Machida M (2010) Adsorption of Zn(II) and Cd(II) ions onto magnesium and activated carbon composite in aqueous solution. Appl Surf Sci 256: 1619-1623.</p> <p>66. Kongsuwan A, Patnukao P, Pavasant P (2009) Binary component sorption of Cu (II) and Pb(II) with activated carbon from Eucalyptus camaldulensis Dehn bark. J Ind Eng Chem 15: 465-470.</p> <p>67. Guo MX, Qiu GN, Song WP (2010) Poultry litter-based activated carbon for removing heavy metal ions in water. Waste Manage 30: 308-315.</p> <p>68. Iijima S (1991) Helical microtubules of graphitic carbon. Nature 354: 56-58.</p> <p>69. Kabbashi NA, Atieh MA, Al-Mamun A, Mirghami MES, Alam MDZ, et al. (2009) Kinetic adsorption of application of carbon nanotubes for Pb (II) removal from aqueous solution. J Environ Sci 21: 539-544.</p> <p>70. Kuo CY, Lin HY (2009) Adsorption of aqueous cadmium (II) onto modified multiwalled carbon nanotubes following microwave/chemical treatment. Desalination 249: 792-796.</p> <p>71. Pillay K, Cukrowska EM, Coville NJ (2009) Multi-walled carbon nanotubes as adsorbents for the removal of parts per billion levels of hexavalent chromium from aqueous solution. J Hazard Mater 166: 1067-1075.</p> <p>72. Kandah MI, Meunier JL (2007) Removal of nickel ions from water by multi-walled carbon nanotubes. J Hazard Mater 146: 283-288.</p> <p>73. Odom TW, Huang JL, Kim P, Lieber CM (1998) Atomic structure and electronic properties of single-walled carbon nanotubes. Nature 391:</p>

<p><b>Citation:</b> Rakhi NM and Dayanand S (2017) Efficient Removal of Heavy metals from Environ Biotechnol 2017: APEB-105</p>	<p>Oil-field Produced Water: A Review of Currently Available Techniques. Arch Petro</p>
<p>62-64.</p> <p>74. Rao G.P, Lu C, Su F (2007) Sorption of divalent metal ions from aqueous solution by carbon nanotubes: a review. <i>Sep Purif Technol</i> 58: 224-231.</p> <p>75. Bhattacharyya KG, Gupta SS (2008) Adsorption of a few heavy metals on natural and modified kaolinite and montmorillonite: a review. <i>Adv Colloid Interface Sci</i> 140: 114-131.</p> <p>76. Wan Ngah SW, Hanafiah MAKM (2008) Removal of heavy metal ions from wastewater by chemically modified plant wastes as adsorbents: a review. <i>Bioresour Technol</i> 99 : 3935-3948.</p> <p>77. Betancur M, Bonelli PR, Velásquez JA, Cukierman AL (2009) Potentiality of lignin from the Kraft pulping process for removal of trace nickel from wastewater: effect of Demineralization. <i>Bioresour Technol</i> 100: 1130-1137.</p> <p>78. Sheng GD, Wang SW, Hua J, Lu Y, Li JX et al. (2009) Adsorption of Pb (II) on diatomite as affected via aqueous solution chemistry and temperature. <i>Colloid Surf.</i> 339: 159-166.</p> <p>79. Mohan D, Chander S (2006) Removal and recovery of metal ions from acid mine drainage using lignite: a low cost sorbent. <i>J Hazard Mater</i> 137: 1545-1553.</p> <p>80. Kohler SJ, Cubillas P, Rodriguez-Blanco JD, Bauer C, Prieto M (2007) Removal of cadmium from wastewaters by aragonite shells and the influence of other divalent cations. <i>Environ Sci Technol</i> 41: 112-118.</p> <p>81. Apiratikul R, Pavasant P (2008) Sorption of Cu<sub>2</sub>, Cd<sub>2</sub> and Pb<sub>2</sub> using modified Zeolite from coal fly ash. <i>Chem Eng J</i> 144: 245-258.</p> <p>82. Al-Jilil SA, Alsewailam FD (2009) Saudi Arabian clays for lead removal in wastewater. <i>Appl Clay Sci</i> 42: 671-674.</p> <p>83. Gu XY, Evans LJ (2008) Surface complexation modelling of Cd(II), Cu(II), Ni(II), Pb(II) and Zn(II) adsorption onto kaolinite. <i>Geochim Cosmochim Acta</i> 72: 267-276.</p> <p>84. Agoubordea L, Navia R (2009) Heavy metals retention capacity of a non-conventional sorbent developed from a mixture of industrial and agricultural wastes. <i>J. Hazard. Mater</i> 167: 536-544.</p> <p>85. Ismail MHS, Zhang XT, Lazim MFM (2013) Removal of Boron and Arsenic from Petrochemical Wastewater by Using Aquatic Booster as Adsorbent, <i>Pol. J. Environ. Stud</i> 22: 403-408.</p> <p>86. Barakat MA, Sahiner N (2008) Cationic hydrogels for toxic arsenate removal from aqueous environment. <i>J. Environ. Manage</i> 88:955–961.</p> <p>87. Aman T, Kazi AA, Sabri MU, Bano Q (2008) Potato peels as solid waste for the removal of heavy metal copper(II) from waste water/industrial effluent. <i>Colloid Surf</i> 63: 116-121.</p> <p>88. Kaczala F, Marques M, Hogland W (2009) Lead and vanadium removal from a real industrial wastewater by gravitational settling/sedimentation and sorption onto <i>Pinus sylvestris</i> sawdust. <i>Bioresour Technol</i> 100: 235-243.</p> <p>89. Saeed A, Iqbal M, Akhtar MW (2005) Removal and recovery of lead(II) from single and multimetal (Cd, Cu, Ni, Zn) solutions by crop milling waste (black gram husk). <i>J Hazard Mater</i> 117: 65-73.</p> <p>90. Srinivasan K, Balasubramaniam N, Ramakrishna TV (1998) Studies on chromium removal by rice husk carbon. <i>Indian J Environ Health</i> 30: 376-387.</p> <p>91. Munaf E, Zein R (1997) The use of rice husk for removal of toxic met-</p>	<p>als from wastewater. <i>Environ Technol</i> 18: 359-362.</p> <p>92. Oliveira L, Franca AS, Alves TM, Rocha SDF (2008) Evaluation of untreated coffee husks as potential biosorbents for treatment of dye contaminated waters. <i>J. Hazard. Mater</i> 155: 507-512.</p> <p>93. Jai PH, Wook JS, Kyu YJ, Gil KB, Mok LS (2007) Removal of heavy metals using waste eggshell. <i>J. Environ. Sci</i> 19: 1436-1441.</p> <p>94. Amudaa OS, Adelowa FE, Ologunde MO (2009) Kinetics and equilibrium studies of adsorption of chromium (VI) ion from industrial wastewater using <i>Chrysophyllum albidum</i> (Sapotaceae) seed shells. <i>Colloid Surf</i> 68:184-192.</p> <p>95. Mata YN, Blázquez ML, Ballester A, González F, Muñoz JA (2009) Sugar-beet pulp pectin gels as biosorbent for heavy metals: preparation and determination of biosorption and desorption characteristics. <i>Chem. Eng. J</i> 150: 289-301.</p> <p>96. Schiewer S, Patil SB (2008) Modeling the effect of pH on biosorption of heavy metals by citrus peels. <i>J. Hazard. Mater</i> 157: 8-17.</p> <p>97. Khan NA, Ali SI, Ayub S (2001) Effect of pH on the removal of chromium (Cr) (VI) by sugar cane baggase, <i>Sci. Technol</i> 6: 13-19.</p> <p>98. Tan WT, Ooi ST, Lee CK (1993) Removal of chromium (VI) from solution by coconut husk and palm pressed fibre, <i>Environ. Technol</i> 14: 277-282.</p> <p>99. Khan NA, Shaaban MG, Hassan MHA (2003) Removal of heavy metal using an inexpensive adsorbent, in: <i>Proc. UM Research Seminar organized by Institute of Research Management and Consultancy (IPPP), University of Malaya, Kuala Lumpur.</i></p> <p>100. Ayub S, Ali SI, Khan NA (2001) Efficiency evaluation of neem (<i>Azadirachta indica</i>) bark in treatment of industrial wastewater, <i>Environ. Pollut. Control J</i> 4: 34-38.</p> <p>101. Ajjabi LC, Chouba L (2009) Biosorption of Cu<sub>2</sub>p and Zn<sub>2</sub>p from aqueous solutions by dried marine green macroalga <i>Chaetomorpha linum</i>. <i>J. Environ. Manage</i> 90: 3485-3489.</p> <p>102. Pavasant P, Apiratikul R, Sungkhum V, Suthiparinyanont P, Wattanachira S, et al. (2006) Biosorption of Cu<sub>2</sub>, Cd<sub>2</sub>, Pb<sub>2</sub>, and Zn<sub>2</sub> using dried marine green macroalga <i>Caulerpalentillifera</i>. <i>Bioresour. Technol</i> 97: 2321-2329.</p> <p>103. El-Sikaily A, Nemr AE, Khaled A, Abdelwehab O (2007) Removal of toxic chromium from wastewater using green alga <i>Ulva lactuca</i> and its activated carbon. <i>J. Hazard. Mater</i> 148: 216-228.</p> <p>104. Deng LP, Su YY, Su H, Wang XT, Zhu XB (2007) Sorption and desorption of lead (II) from wastewater by green algae <i>Cladophora fascicularis</i>. <i>J. Hazard. Mater</i> 143: 220-225.</p> <p>105. Pan JH, Liu RX, Tang HX (2007) Surface reaction of <i>Bacillus cereus</i> biomass and its biosorption for lead and copper ions. <i>J. Environ. Sci</i> 19: 403-408.</p> <p>106. Souiri M, Gammoudi I, Ouada HB, Mora L, Jouenne T, et al. (2009) <i>Escherichia coli</i>-functionalized magnetic nanobeads as an ultrasensitive biosensor for heavy metals. <i>Proced. Chem</i> 1: 1027-1030.</p> <p>107. Gabr RM, Hassan SHA, Shoreit AAM (2008) Biosorption of lead and nickel by living and non-living cells of <i>Pseudomonas aeruginosa</i> ASU 6a. <i>Int. Biodeterior. Biodegradation</i> 62: 195-203.</p> <p>108. Amini M, Younesi H, Bahramifar N (2009) Statistical modeling and optimization of the cadmium biosorption process in an aqueous solution</p>

<p><b>Citation:</b> Rakhi NM and Dayanand S (2017) Efficient Removal of Heavy metals from Environ Biotechnol 2017: APEB-105</p>	<p>Oil-field Produced Water: A Review of Currently Available Techniques. Arch Petro</p>
<p>using <i>Aspergillus niger</i>. <i>Colloid Surf</i> 337: 67-73.</p> <p>109. Aksu Z, Balibek E (2007) Chromium(VI) biosorption by dried <i>Rhizopus arrhizus</i>: effect of salt (NaCl) concentration on equilibrium and kinetic parameters. <i>J. Hazard. Mater</i> 145: 210-220.</p> <p>110. Chen C, Wang JL (2008) Removal of Pb<sub>2</sub>, Ag, Cs and Sr<sub>2</sub> from aqueous solution by brewery's waste biomass. <i>J. Hazard. Mater</i> 151: 65-70.</p> <p>111. Bayramoglu G, Arica MY (2008) Removal of heavy mercury (II), cadmium(II) and zinc(II) metal ions by live and heat inactivated <i>Lentinus edodes</i> pellets. <i>Chem. Eng. J</i> 143: 133-140.</p> <p>112. Landaburu-Aguirre J, Pongrácz E, Perämäk P, Keiski RL (2010) Micell-enhanced ultrafiltration for the removal of cadmium and zinc: use of response surface methodology to improve understanding of process performance and optimisation. <i>J. Hazard. Mater</i> 180: 524-534.</p> <p>113. Shahalam AM, Al-Harthy A, Al-Zawhry A (2002) Feed water pretreatment in RO systems in the Middle East. <i>Desalination</i> 150: 235-245.</p> <p>114. ohsen-Nia M, Montazeri P, Modarress H (2007) Removal of Cu<sub>2</sub> and Ni<sub>2</sub> from wastewater with a chelating agent and reverse osmosis processes. <i>Desalination</i> 217: 276-281.</p> <p>115. Murthy ZVP, Chaudhari LB (2008) Application of nanofiltration for the rejection of nickel ions from aqueous solutions and estimation of membrane transport parameters. <i>J. Hazard. Mater</i> 160: 70-77.</p> <p>116. Muthukrishnan M, Guha BK (2008) Effect of pH on rejection of hexavalent chromium by nanofiltration. <i>Desalination</i> 219: 171-178.</p> <p>117. Cséfalvai E, Pauer V, Mizsey P (2009) Recovery of copper from process waters by nanofiltration and reverse osmosis. <i>Desalination</i> 240: 132-142.</p> <p>118. Nguyen CM, Bang S, Cho J, Kim KW (2009) Performance and mechanism of arsenic removal from water by a nanofiltration membrane. <i>Desalination</i> 245: 82-94.</p> <p>119. Erikson P (1988) Nanofiltration extends the range of membrane filtration. <i>Environ. Prog</i> 7: 58-62.</p> <p>120. Sadrzadeha M, Mohammadi T, Ivakpour J, Kasiri N (2009) Neural network modeling of Pb<sub>2</sub> removal from wastewater using electro dialysis. <i>Chem. Eng. Process</i> 48: 1371-1381.</p> <p>121. Lundh M, Jönsson L, Dahlquist J (2000) Experimental studies of the fluid dynamics in the separation zone in dissolved air flotation. <i>Water Res</i> 34: 21-30.</p> <p>122. Polat H, Erdogan D (2007) Heavy metal removal from waste waters by ion flotation. <i>J. Hazard. Mater</i> 148: 267-273.</p> <p>123. Yuan XZ, Meng YT, Zeng GM, Fang YY, Shi JG (2008) Evaluation of tea-derived biosurfactant on removing heavy metal ions from dilute wastewater by ion flotation. <i>Colloid Surf</i> 317: 256-261.</p> <p>124. Capponi F, Sartori M, Souza ML, Rubio J (2006) Modified column flotation of adsorbing iron hydroxide colloidal precipitates. <i>Int. J. Miner. Process</i> 79: 167-173.</p>	<p>125. Chen GH (2004) Electrochemical technologies in wastewater treatment. <i>Sep. Purif. Technol</i> 38: 11-41.</p> <p>126. Heidmann I, Calmano W (2008) Removal of Zn (II), Cu(II), Ni(II), Ag(I) and Cr(VI) present in aqueous solutions by aluminium electrocoagulation. <i>J. Hazard. Mater</i> 152: 934-941.</p> <p>127. Khodir M, Belkacem M, Abdelkrim S (2008) Treatment characteristics of textile wastewater and removal of heavy metals using the electroflotation technique. <i>Desalination</i> 228: 245-254.</p> <p>128. Issabayeva G, Aroua MK, Sulaiman NM (2006) Electrodeposition of copper and lead on palm shell activated carbon in a flow-through electrolytic cell. <i>Desalination</i> 194: 192-201.</p> <p>129. Herrmann JM (1999) Heterogeneous photocatalysis: fundamentals and applications to the removal of various types of aqueous pollutants. <i>Catal. Today</i> 53: 115-129.</p> <p>130. Barakat (2005) Adsorption behavior of copper and cyanide ions at TiO<sub>2</sub>-solution interface. <i>J Colloid Interface Sci</i> 291: 345-352.</p> <p>131. Zhang FS, Itoh H (2006) Photocatalytic oxidation and removal of arsenite from water using slag-iron oxide-TiO<sub>2</sub> adsorbent. <i>Chemosphere</i> 65:125-131.</p> <p>132. Hassani AH, Hossenzadeh I, Torabifar B (2010) Investigation of Using Fixed Activated Sludge System for Removing Heavy Metals (Cr, Ni and Pb) From Industrial Wastewater. <i>Journal of Environmental Studies</i> 36: 22-24.</p> <p>133. Pagnanelli F, Mainelli S, Bornoroni L, Dionisi D, Toro L (2009) Mechanisms of heavy-metal removal by activated sludge <i>Chemosphere</i> 75: 1028-1034.</p> <p>134. Srivastava NK, Majumder CB (2008) Novel bio filtration methods for the treatment of heavy metals from industrial wastewater. <i>J Hazard Mater</i> 151: 1-8.</p> <p>135. Dermou E, Velissariou A, Xenos D, Vayenas DV (2005) Biological Chromium (VI) Reduction using a trickling filter. <i>Journal of Hazardous Materials</i>: 78-85.</p> <p>136. Ito A, Takahashi K, Aizawa J, Umita T (2008) Enhanced heavy metals removal without phosphorus loss from an aerobically digested sewage sludge. <i>Water Sci Technol</i> 58: 201-206.</p> <p>137. Polprasert C, Charnpratheep K (1989) Heavy metal removal by attached growth waste stabilization pond. <i>Water Res</i> 23: 625-631.</p>